



American Specialties, Inc.

BERLS.COM

Model #0462-AD-9

Technical Data Sheet

Paper Towel Dispenser & Waste Receptacle – Surface Mounted

Paper Towel Combination Units

Traditional

MasterFormat Section 10 28 13



Scan for Information





MR 4.1 (1) EQ 4.1 (1) MR 4.2 (1) EQ 4.2 (1) MR 6 (1) EQ 4.4 (1)

7/32" DIA [Ø5,5] MOUNTING HOLES 7/32" DIA [Ø5.5] MOUNTING HOLES
BACK PANEL REAR PANEL [108] [102] 3" [76] 2" [51] CONTINUOUS STAINLESS 1-1/2" [38] TUMBLER ROLLED EDGE 9-3/4 [248] 2" [51] REMOVABLE WASTE STAINI ESS

> ALL DIM'S INCH [MM] ILLUSTRATION FOR REF ONLY AND NTS

FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

PRODUCT OVERVIEW

Dispenses 350 C-fold or 475 multi-fold paper towels. 2 gal. (7.6 L) waste receptacle. Surface mounted with stainless steel collar.

KEY FEATURES & SPECIFICATIONS

- Double-pan construction door has "no-Flex" fiberboard filler for added rigidity and strength
- Door is attached to the cabinet with a 3/16" diameter [Ø5] Heavy-duty, Multi-Staked Stainless Steel Piano Hinge
- 22 gauge Type 304 Stainless Steel Satin Finish
- Surface Mounted w/ -9 Collar
- 350 C-Fold or 475 Multi-Fold / 2.0 Gal. (7.6 L) Waste Capacity

American Specialties, Inc. Saw Mill River Road, Yonkers, NY 10701 (914)476-9000 www.americanspecialties.com Model:#0462-AD-9 Revision: R3 Issued: 11/1/2021 Revised: 9/11/2023

CSI:10 28 13 **Toilet Accessories**

Page: 1 of 2





Model #0462-AD-9

Technical Data Sheet

OPERATION & MAINTENANCE

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly. Waste container is emptied manually on cycle determined by maintenance needs.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	14-1/14" [362] W x 28" [711] H x 4-1/4" [108] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Surface Mounted - w/ -9 Collar
Capacity	350 C-Fold or 475 Multi-Fold / 2.0 Gal. (7.6 L) Waste Capacity

INSTALLATION

Surface mount unit to wall using #10 self-threading screws (by others) through concealed mounting holes provided. For compliance with 2010 ADA Accessibility Standards mount unit with centerline of towel outlet 48" [1219] maximum Above Finish Floor (AFF). SM collar is installed on cabinet prior to mounting on wall following procedure described on SM Collar Data Sheet.

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #0462-AD-9

Revision: R3 Issued: 11/1/2021 Revised: 9/11/2023