1-3/8

[35]

5-1/4" [133]





**BERLS.COM** 

## Model #0827

#### **Technical Data Sheet**

## Waste Receptacle (2 gal.) – Surface Mounted

Waste Receptacles

MasterFormat Section 10 28 13










MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1) 10-1/2" [267]

Q
1-1/2" [191]

(38)

FINISHED WALL



NOTE:
ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

## Product Overview

Holds 2 gallons (7.6 liters) of waste material. Unit provided with four (4) 'key hole' slots on rear for hanging on preinstalled screws. Waste material is deposited into the receptacle through the open top. Use of a disposable trash liner bag is recommended. Unit on concealed 'key hole' slots may be lifted off mounting screws for dumping. Unit shall be 22 gauge type 304 stainless steel alloy 18-8 with satin finish and be protected during shipment with a PVC film easily removable after installation.

### KEY FEATURES & SPECIFICATIONS

- Has interior hooks for hanging a resuable bag (sold seperately)
- Type 304 Stainless Steel Satin Finish
- Screw Mounted to Wall
- Surface Mounted
- 2.0 Gal. (7.6 L) Waste Capacity

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#0827 Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023

CSI: 10 28 13 Toilet Accessories Page: 1 of 2





## Model #0827

**Technical Data Sheet** 

#### **OPERATION & MAINTENANCE**

Waste material is deposited into the receptacle through the open top. Waste material is removed on a cycle determined by maintenance needs. Use of a disposable trash liner bag is recommended. Unit on concealed 'key hole' slots may be lifted off mounting screws for dumping.

# **TECHNICAL INFORMATION / PRODUCT PROPERTIES**

Property	Value
Dimensions	10-1/2" [267] W x 9" [229] H x 4-3/4" [121] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Screw Mounted to Wall
Capacity	2.0 Gal. (7.6 L) Waste Capacity

### INSTALLATION

For general utility, mount receptacle 30" [762] Above Finished Floor (AFF) from bottom of unit. Hang unit on (4) #10 screws (by others) on wall through concealed mounting 'key hole' slots. For compliance with 2010 ADA Accessibility Standards, install unit with top edge no higher than 48" [1219] Above Finished Floor (AFF).

### **O**PTIONS

N/A

#### WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #0827 Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023