



Model #6459

Technical Data Sheet

Simplicity™ Collection Waste Receptacle – Recessed

BERLS.COM

Waste Receptacles

Simplicity

MasterFormat Section 10 28 13




Scan for Information





MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

4-1/2" [114] 14-1/4" [362] 1-1/4" [32] 1" [25] 1" [25] TYP INTERNATIONAL 5" [127 GRAPHIC 1" [25] WASTE SYMBOL PIANO HINGE 28" [660] [711] REMOVABLE WASTE: RECEPTACLE TUMBLER LOCK 7/32" DIA [Ø6] MOUNTING HOLES TYP " [25] 1/2" [13] -1-3/4" [44]



NOTE:
ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

Product Overview

Stainless steel waste receptacle holds 4 gal. (15 L) of waste and has a self-closing panel that covers its opening. Cabinet door held closed with a tumbler lock. Waste container fabricated of heavy duty corrosion resistant steel with a handle for easy grip. Waste is inserted through self-closing push door. Locked compartment prevents unauthorized access. Full face door shall be formed from one piece of 18 gauge alloy 18-8 type 304 stainless steel, cabinet shall be 20 gauge same grade stainless steel with no fastening devices or spot welded seams.

KEY FEATURES & SPECIFICATIONS

- Seamless construction, crisp lines and minimalistic design
- Type 304 Stainless Steel Satin Finish
- Recessed
- Push door has self-closing spring
- 4.0 Gal. (15.0 L) Waste Capacity

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#6459

Revision: R1 | Issued: 11/1/2021 | Revised: 3/10/2023

CSI: 10 28 13 Toilet Accessories Page: 1 of 2



Model #6459

Technical Data Sheet

OPERATION & MAINTENANCE

Waste is inserted through self-closing push door. Waste container is emptied manually on cycle determined by maintenance needs. Locked compartment prevents unauthorized access.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	14-1/4" [362] W x 28" [711] H x 4-1/2" [114] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Recessed
Capacity	4.0 Gal. (15.0 L) Waste Capacity

INSTALLATION

Mount unit in wall recess or partition using #10 self-threading screws (by others) through concealed mounting holes. For compliance with 2010 ADA Accessibility Standards, install unit with top edge no higher than 48" [1219] Above Finished Floor (AFF).

Rough Wall Opening (RWO) required is 12-3/4" [324] W x 26-1/2" [673] H x 4-1/4" [108] D minimum

OPTIONS

N/A

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#6459

Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023