SLOAN®

DropSpot™ Bottle Filler & Water Cooler

DRS110

Product description

, DropSpot™ On-wall Bottle Filler with Single-level Cooler.

Compliances & Certifications

ASME c UL us LISTED UPC FC IAPMO MEMBER UPC NSF-372 UL LISTED

(ASME A112.18.1 Compliant, FCC Compliant, IAPMO, IAPMO listed ASME, IGC 115, IGC 226, MA Approved, Meets Canada OBC and QBC, NSF-61/CAN-61, NSF-372 Lead Free, AB100, NSF/ANSI/CAN 61: Q ≤ 1.0, TAS, UL 399/CSA C22.2 No.120, UL Certified (US and Canada), cUPC Certified)

Code 33820026

Finish

Black (BLK)

Downloads

- DRS110_DRS115 Refrigerated Single Level Cooler Installation Instructions.pdf
- DRS110_DRS115 Unrefrigerated Single Level Cooler Installation Instructions.pdf
- FA3000 DRS110_115_120_125 Drop Down Filter Assembly Installation Instructions.pdf
- FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf
- DropSpot Bottle Fillers and Water Coolers Brochure.pdf
- DropSpot™ Care and Cleaning Guide.pdf
- Additional Downloads

Videos

- Sloan DropSpot™ Bottle Fillers and Water Coolers
- Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Product Information

DRS110

Details

- Mounting: On-wall
- Configuration: Bottle Filler with Single-level Cooler
- Filter Option: Unfiltered (UNFIL)
- Refrigeration Option: Refrigerated (REF)
- Finish: Black (BLK)
- Chilling Capacity: 8.0 gph (30.3 Lph)
- Full Load Amps: 5.3
- Length: 19 (483mm)
- Width: 19 (483mm)
- Height: 39.6 (1006mm)
- Weight: 84lbs (38kg)
- Installation Location: Indoor
- Stations Served: 1
- Bottle Filler Water Flow Rate: Up to 1.2 gpm (4.5 Lpm)
- Bubbler Flow Rate: 0.3 gpm (1.1 Lpm)

Features

Sloan Single Station Bottle Filler Drinking Fountain Combo available in both Stainless and Black, filtered and unfiltered, refrigerated and unrefrigerated options.

- Touch-free sensor operated bottle filler with 20 second max run time, Up to 1.2 gpm fill rate for quick fill with laminar flow
- All models SC Argus® Pro compatible for remote water monitoring, filter alerts, automated line-flush scheduling, and documentation across one or multiple facilities; subscription required
- ADA compliant when installed properly
- Backlit LED light that illuminates bottle filling area when sensor is activated, Soft ambient white light to indicate filter status
- Bottle Counter Display indicates the number of 16 oz plastic bottles saved as well as ounces of water dispensed
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement
- Antimicrobial bubbler, push bar, and other components
- Drop-down door assembly provides easy access to filter
- Patent pending push bar designed to be activated at any touch point and to provide easy access for cartridge replacement
- OPTIONAL: A water filter upgrade can be added to this unit (part number 33830002). Sold separately

Recommended specifications

Sloan's DropSpot™ On-wall Bottle Filler with Single-level Cooler Unfiltered Refrigerated black powder coat. Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient. Unit shall be activated from an antimicrobial front pushbar using less than 5 pounds of force. Bubbler shall deliver a 0.3 gpm flow. Basin and cabinet shall be constructed from galvannealed steel with black powder coat finish. Bottle filler shall include sensor operated activation with a 20 second maximum run time. Bottle counter display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking. Unit shall include a LED light that illuminates the bottle filling area. Bottle filler housing construction shall be galvannealed steel with black powder coat finish. Bottle filler shall provide up to 1.2 gpm flow rate with a laminar flow. Push bar shall be activated by any touch point on the bar and shall be opened by Sloan access key.

Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Duplex Receptacle on GFCI Protected Circuit

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Rough-in and line drawing

DRS110

Prior to roughing in, consult local, state, and federal codes for proper mounting height.