

SPECIFICATION

Towel Pin unit shall be fabricated of stainless steel alloy 18-8, type 304. Pin post shall be $1/2" \times 1" (13mm \times 25mm)$ rectangular tubing with formed mounting flange and bracket welded on end. Cap plate shall be $3/4" \times 1-1/2" (19mm \times 38mm)$ welded to outer end. Mounting plate shall be included and shall be 18 gauge. A stainless steel setscrew shall be provided on bottom perimeter of flange to lock unit to mounting plate. Surface finish shall be bright or satin as chosen by option and indicated by code suffix.

Towel Pin unit shall be Model № 7301-B or № 7301-S of American Specialties, Inc., 441 Saw Mill River Road, Yonkers, New York 10701-4913

INSTALLATION

ERĽS

Surface mount unit on door or wall using Nº 10 self tapping screws (by others) through holes provided in mounting plate into suitable prepared mountings (by others) or other suitable mounting hardware (by others) to suit door or wall conditions. Hang post and flange assembly on mounting plate and tighten setscrew to lock unit to plate. For compliance with ICC/ANSI A-117.1-2003 and ADA Accessibility Guidelines install unit with top of towel pin 48" (1219mm) maximum above finished floor (MAX AFF) if clear floor forward reach or if clear floor side reach access only is provided or 46" (1168mm) MAX AFF if side reach access over an obstruction (e.g. vanity) with reach depth greater than 10" (254mm) and less than 25" (635mm) is only provided or 44" (1118mm) MAX AFF if forward reach over an obstruction with reach depth greater than 20" (508mm) and less than 25" (635mm) is only provided. For general utility install pin with centerline of mounting plate between 55" and 68" (1397mm to 1727mm) AFF.

Accessory Specialties	AMERICAN DISPENSER	Desert Ray Products	
-----------------------	--------------------	---------------------	--

THIS MANUFACTURER RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN OR DIMENSIONS WITHOUT FORMAL NOTICE