

Halsey Taylor HydroBoost Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered Non-Refrigerated Stainless

Model HTHBHVR-NF

PRODUCT SPECIFICATIONS

Halsey Taylor HydroBoost® Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered Non-Refrigerated Stainless. Features shall include Green Counter™, Laminar Flow, Real Drain, Vandal Resistant. Furnished with Vandal Resistant bubbler. Electronic Bottle Filler Button with Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

Special Features:	Green Counter™, Laminar Flow, Real Drain, Vandal Resistant
Finish:	Stainless Steel
Power:	115V/60Hz
Bubbler Style:	Vandal Resistant
Activation by:	Electronic Bottle Filler Button with Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity:	Non-refrigerated
Full Load Amps	1
Rated Watts:	15
Dimensions (L x W x H):	18" x 18-5/8" x 38-13/16"
Approx. Shipping Weight:	48 lbs.
Installation Location:	Indoor + Outdoor
No. of Stations Served:	1

**When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Green Counter: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- Real Drain System eliminates standing water.

PART:	QTY:	
PROJECT:		
CONTACT:		
DATE:		
NOTEO:		



Included with Product:

Water Cooler (CLR-HTHBHVR-NF), **Bottle Filler (HVRHTHB-NF)**

▼ Ships in multiple boxes.

AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

Buy American Act

CAN/CSA C22.2 No. 120

GreenSpec®

NSF/ANSI 61 & 372 (lead free)

UL 399









Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF)

Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

RESTROOMDIRECT

APPROVAL:



Halsey Taylor HydroBoost Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered Non-Refrigerated Stainless

_	3		-	_		_		
Mo	del	HT	HB	31	IVR	-1	۷F	

Optional Accesso	ries	
HWF3000	Halsey Taylor WaterSentry Plus Filter Kit (Bottle Fillers) Spec Sheet (PDF)	
MLP100	In-wall Carrier for Single-station On-wall Bottle Fillers, Coolers & Fountains Spec Sheet (PDF)	H
<u>98324C</u>	Accessory - Cane Apron for HAC HVR EMABF & VRC Models (Stainless) Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Halsey Taylor HydroBoost Vandal-Resistant Bottle Filling Station & Single ADA Cooler Non-Filtered Non-Refrigerated Stainless **Model HTHBHVR-NF**

OPERATION OF QUICK CONNECT FITTINGS IMPORTANT! **INSTALLER PLEASE NOTE:**

This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways. The grounding of electrical equipment such as telephone, computer, etc. to water lines is a common procedure. The grounding may be in the building but may also occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown

NOTICE

This water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.

Bottle filler unit on bracket attached to wall by 6 holes (as shown). Water and electrical

will connect through pre-punched hole in basin.

These products are designed to operate on 20 psi to 105 psi supply line pressure

Simply push in |Tube is secured |Push in collet to tube to attach in position release tube Pushing tube in before

pulling it out helps to

release tube

1/4" O.D. tube 3/8" O.D. Tube connect Building water water inlet to cold water supply inlet cooler 40 Servicé stop NOTE: Waterflow (Not furnished) direction

18-5/8" 16-5/16 (414mm) (472mm) Ø 5/16" 5-1/8" (8mm) — MOUNTING (178mm) (178mm) (131mm) HOLES (3PL) 51-1/8" (1298mm) HANGER 18-1/2" BRACKET (470mm) 2-5/8 1/4" 1/2" (6mm x 13mm) OBROUND HOLE (5PL) (66mm) 48' 1-1/4" 1-1/4" (1219mm) (32mm) _I (32mm) e e _4-9/16" (116mm) E-33-1/16" (840mm) ORIFICE 49-1/2" (1257mm) HEIGHT + 🗍 (203mm) 3/4" + (18mm) 2-1/2" 7-1/4" (185mm) 31-15/16" (811mm) D. (64mm) 31' (788mm) HEIGHT (635mm) 2-7/16 (63mm) 1-1/2" 21-3/8 (686mm) (38mm) 3-1/2 (543mm) 2-9/16" ADA REQUIREMENT (89mm) 4-1/2 6-1/4" (65mm) 18-3/8" 13-7/8" (352mm) (159mm)(114mm) 12-5/16" (467mm) 10" (313mm)6-3/4 (127mm) (254mm) (171mm) FINISHED FLOOR FINISHED FLOOR REDUCE HEIGHT BY 3" FOR INSTALLATION OF CHILDREN'S ADA COOLER

A = Recommended Water Supply location. Shut-off Valve (not furnished) to accept 3/8" O.D. unplated copper tube. Up to 3" (76mm) maximum out from wall. B = Recommended Waste Outlet location. To accommodate 1-1/4" nominal drain. Drain stub 2" (51mm) out from wall.

C = 1-1/4" Trap (not furnished)

D = Electrical Supply (3) Wire Recessed Box Duplex Outlet.
E = Insure proper ventilation by maintaining 6" (152mm) minimum clearance from cabinet louvers to wall.
F = 7/16" (11mm) Bolt Holes for fastening to wall.

Note: New Installations Must Use Ground Fault Circuit Interrupter (GFCI). It is highly recommended that the circuit be dedicated and the load protection be sized for 20 amps

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit Halseytaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

RESTROOMDIRE