BERLS.COM BERLS.COM (800) 409-3131



BASYS® SENSOR FAUCET

EFX-250-BAT-BDT-CP-1.5GPM-FCT (General Model Name: EFX250.202.0000)



This item has shipping restrictions due to state regulations and cannot be shipped to California, Colorado, Hawaii, Maine, New York, Oregon, and Washington.

CODE NUMBER

3324258

DESCRIPTION

Trim Plate: None, Battery Power Supply, Below Deck Thermostatic Mixing Valve, Polished Chrome Finish, 1.5 gpm, Aerated (installed) or Laminar (in box) Spray, Infrared Sensor, BASYS® Battery-Powered Deck-Mounted Mid Body Faucet.

DETAILS

• Flow Rate: 1.5 gpm (5.7 Lpm) (1.5GPM)

• Spray Type: Aerated (installed) or Laminar (in box)

Sensor Type: InfraredMounting Type: Single Hole

• Trim Plate: None

• Power Supply: Battery (BAT)

• Temperature Mixer: Below Deck Thermostatic Mixing Valve (BDT)

• Finish: Polished Chrome (CP)

Factory Default Timeout: 10 secondsFactory Default Gallons per Cycle: 0.75

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-CastMetal Hand Washing Faucet with the following features:

- · One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- Standard Bowed Crown

ELECTRICAL SPECIFICATIONS


- Battery Life: 3 years 8,000 cycles/month
 Optional power harvesting significantly extends service life
- Sensor Range: 4"-5" (102-127mm)

VIDEOS



BASYS® Faucet Installation and Features





COMPLIANCES & CERTIFICATIONS

























(ADA Compliant, ASME A112.18.1 Compliant, ASSE 1070, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, EPD, HPD, IAPMO, Proposition 65, TAS, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL Building Standard)

RECOMMENDED SPECIFICATION

Sloan BASYS Model No. EFX-250-BAT-BDT-CP-1.5GPM-AER-IR-FCT Infrared Sensor Activated Electronic Handwashing Faucet for pretempered or hot/cold water supplies. Product to have double infrared sensors with automatic setting feature. Solenoid valve housed in removable carrier that closes water

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



BERLS.COM (800) 409-3131

SLDAN

BASYS® SENSOR FAUCET EFX-250-BAT-BDT-CP-1.5GPM-FCT

(General Model Name: EFX250.202.0000)

BASYS® Faucet Installation Mid Height Model

PVD Special Finishes

Sloan Connect App®

DOWNLOADS

- EFX 1Xx/2Xx Installation Instructions
- EFX 1Xx/2Xx Caddy Replacement Installation Instructions
- Trim Plate Guide
- IR FAQs Repair and Maintenance Guide
- EFX-2XX Repair and Maintenance Guide
- Faucet Spray Heads Repair and Maintenance Guide
- IR FAQs SP Repair and Maintenance Guide
- Additional Downloads

supply upon removal eliminating, need to access control stops. Solenoid carrier includes strainer for easy above deck service. Thermostatic mixer ordered separately to comply with ASSE 1070 requirements. The product shall be tested and certified to industry standards: ASME A112.18.1M, CSA B125.1, California Health and Safety Code 116875

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EFX-250 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

View Warranty Information





SLOAN.

BASYS® SENSOR FAUCET EFX-250-BAT-BDT-CP-1.5GPM-FCT

(General Model Name: EFX250.202.0000)

ROUGH-IN

EFX-250.00X.XXXX Faucet with Single Line Water Supply

EFX-250.50X.XXXX Faucet with Hot and Cold Water Supply

