BERLS.COM



OPTIMA® SENSOR FAUCET EAF-150-BAT-CP-1.5GPM-AER-IQ-FCT

(General Model Name: EAF150 CP BATTERY FAUCET (IQ))

CODE NUMBER

3335000

DESCRIPTION

Battery Power Supply, Mixer Not Included, Polished Chrome Finish, 1.5 gpm, Aerated Spray, Infrared Sensor, Optima® Battery-Powered Deck-Mounted Mid Body Faucet.

DETAILS

- Flow Rate: 1.5 gpm (5.7 Lpm) (1.5GPM)
- Spray Type: Aerated (AER)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Power Supply: Battery (BAT)
- Temperature Mixer: Mixer Not Included
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 30 seconds
- Factory Default Gallons per Cycle: 0.75

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Cast Brass Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setup and Indicator Light
- Automatic Self-adapting Sensor Technology
- Low Battery Indicator
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 Volt Lithium 2CR5 Commercial Battery included
- Appropriate Mounting Hardware included
- Optional 24 Hour Sentinel Activation
- IQ-Click feature permits activation of continuous run and temporary off modes


ELECTRICAL SPECIFICATIONS


- Battery Life: 3 years 8,000 cycles/month
 Optional power harvesting significantly extends service life
- Sensor Range: 4"-5" (102-127mm)
- Timeout Adjustment Settings: 30s

DOWNLOADS

- EAF 100/150 Installation Instructions
- EAF 100/150 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 150 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads







COMPLIANCES & CERTIFICATIONS



(ADA Compliant, ASME A112.18.1 Compliant, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, EPD, HPD, IAPMO, Proposition 65, TAS, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL Building Standard)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EAF-150 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

View Warranty Information

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com **BERLS.COM**




OPTIMA® SENSOR FAUCET EAF-150-BAT-CP-1.5GPM-AER-IQ-FCT

(General Model Name: EAF150 CP BATTERY FAUCET (IQ))

EAF-150-ISM, EAF-150-ISM-IC AND

ROUGH-IN



EAF-150-ISM-DPU-IC Faucets with Hot and Cold Water Supply MIXING LEVER Õ SPOUT (Can Be Set and Removed) 1-3/16" (30 mm) MIN. DIA. HOLE 0-RING REQUIRED SLOAN 1-1/2" (38 mm) MAX. DECK GASKET THICKNESS RETAINER NUT 13" (330 mm) LONG FLEX HOSES HOT SUPPLY COLD SUPPLY

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com