ERL'S COMMERCIAL BERLS.COM (800) 409-3131



SLOAN® SENSOR FAUCET SF-2950-4-BAT-TEE-CP-0.5GPM-MLM-FCT

CODE NUMBER

33621005

DESCRIPTION

4" Trim Plate, Battery Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Sloan® Battery-Powered Deck-Mounted Mid Body Faucet.

DETAILS

Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
Spray Type: Multi-Laminar (MLM)

Spout Type: Pedestal
Sensor Type: Infrared
Mounting Type: Single Hole
Trim Plate: 4" (102mm) (4)
Power Supply: Battery (BAT)

• Temperature Mixer: Back-Check Tee (TEE)

Finish: Polished Chrome (CP)
 Factory Default Timeout: 30 seconds
 Factory Default Gallons per Cycle: 0.25

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Gooseneck Hand Washing Faucet with the following features:

• Adjustable Infrared Sensor Range

• 36" (914 mm) Long Sensor Cable

• 24" (610 mm) Long Flex Hose

• Filtered Solenoid Valve with serviceable Strainer Filter

• Includes Four (4) AA-size Batteries

• Includes appropriate Mounting Hardware

ELECTRICAL SPECIFICATIONS


• Battery Life: 2 years 8,000 cycles/month

• Timeout Adjustment Settings: 30s

DOWNLOADS

- SF Series Installation Instructions
- SF Series (FR) Installation Instructions
- SF Series (SP) Installation Instructions
- SFP 35-A Installation Instructions
- Trim Plate Guide
- Faucet Spray Heads Repair and Maintenance Guide
- SF 2900/2950 Repair and Maintenance Guide
- Additional Downloads





COMPLIANCES & CERTIFICATIONS





























(ADA Compliant, ASME A112.18.1 Compliant, CalGreen Compliant, CEC Compliant, cUPC Certified, cUPC Low Lead Compliant, GPC 0.25 or less, IAPMO, NSF-61, NYC604.4, Proposition 65, TAS, UPC Certified, UPC Low Lead Compliant, WaterSense Listed, WELL Building Standard)

RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, Alkaline batteries and 0.5gpm multilaminar spray head.

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the SF-2950 product? View the general spec sheet with all options.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



BERLS.COM

(800) 409-3131

SLOAN® SENSOR FAUCET SF-2950-4-BAT-TEE-CP-0.5GPM-MLM-FCT



Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

WARRANTY

View Warranty Information





ROUGH-IN

