

#### **CODE NUMBER**

3366124

#### **DESCRIPTION**

Sloan® XLERATOR® Sensor-Operated Wall Hand Dryer EHD-502 208/277V

#### **DETAILS**

Finish: Graphite (GR)
Voltage: 208/277V
Wattage: 50/60Hz
Amperage: 5.6-6.2
Mounting: Wall

Power Type: Hardwired
Depth: 12 86/125" (322mm)
Height: 6 11/16" (170mm)
Width: 11 ¾" (298mm)


#### **FEATURES**


- Automatically operates by means of an Infrared Optical Sensor with 35-second lockout feature, it activates a strong controlled air blast
- Residual moisture is evaporated with a warm stream of air up to 135°F/57°C
- One-piece heavy-duty rib reinforced die cast zinc alloy housing minimizes damage to dryer in abusive environments
- 95% cost savings vs. paper towels
- Can be easily positioned to comply with ADA requirements or for juvenile height
- 10 second dry time
- Hygienic hand dryer solution
- Available in Polished White, Matte White, Polished Chrome, Brushed Nickel and Graphite
- · Virtually maintenance free
- Available with Recess Kit for ADA compliance

## **DOWNLOADS**

- Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions
- Additional Downloads







# **COMPLIANCES & CERTIFICATIONS**













(BAA Compliant, BABAA Compliant, cUL Certified, EPD, Proposition 65, UL Certified)

### RECOMMENDED SPECIFICATION

Sloan Xlerator Sensor Operated Hand Dryer. 208V/230V Graphite Finish.

## **NOTES**

All information contained within this document subject to change without notice.

## WARRANTY

**View Warranty Information** 

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com