



Exposed Sensor Flush Valve for Urinal  
**ZER6003PL-SM**

TAG \_\_\_\_\_

**ARCHITECTURAL & ENGINEERING SPECIFICATION**

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with chloramine resistant, dual seal diaphragm with a clog resistant by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button and 10 degree angled sensor.

**PRODUCT FEATURES**

- Control Stop has internal siphon-guard protection, sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Clog resistant by pass
- Adjustable tailpiece
- Spud coupling and flange for top spud connection
- True mechanical override button

**COMPLIANCE AND CERTIFICATION:**

- ADA Compliant
- WaterSense Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



**FLOW OPTIONS**

|                  | FLUSH VOLUME GPF | WATERSENSE* COMPLIANT |
|------------------|------------------|-----------------------|
| <b>-ULF</b>      | 0.125            | ☑                     |
| <b>-EWS</b>      | 0.5              | ☑                     |
| <b>-WS1</b>      | 1.0              |                       |
| <b>-STANDARD</b> | 1.5              |                       |

**VALVE HEIGHT OPTIONS**

|                  | DIMENSION A INCH [MM] | DIMENSION B INCH [MM] |
|------------------|-----------------------|-----------------------|
| <b>-STANDARD</b> | 11 1/2" [292]         | 9 7/8" [251]          |
| <b>-1</b>        | 16" [406]             | 14 3/8" [365]         |
| <b>-2</b>        | 24" [610]             | 22 3/8" [568]         |
| <b>-3</b>        | 27" [686]             | 25 3/8" [645]         |

**SUFFIX OPTIONS**

- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



TAG \_\_\_\_\_

**Rough-in/Overview dimensions:**

